

Model:

NDC-36-SG

Square Cold Showcase

NDC-36-SG



● Cabinet Construction

● Exterior- black brushed stainless steel, high-end and elegant; Interior-mirror s/steel 304, for food sanitation; Foamed with polyurethane, high-density insulation of inner cabinet

● **The front panel and two side panels of base are detachable for easy maintenance**

● **Ultra-clear transparent tempered glass**, high visibility; front glass, top glass, two side glass with **heating film** for anti-fog

● **Refrigeration system:** ventilation and strong cooling; environment-friendly **R290** refrigerant; temperature in cabinet keeps 34°F to 41°F (2°C to 5°C) . It is recommended to be used indoors where ambient temperature and relative humidity do not exceed 80° F(27°C) and 60%.

● **Digital temperature controller** with two probes assuring defrost control to keep the cabinet temperature even during defrosting.

● **Anti-corrosion coated evaporator**

● **Shelf:** stainless steel holder support tempered clear glass shelf, strong bearing. The height and angle are adjustable.

● Each shelf with **LED light**, energy-saving

● **Heavy duty caster**, convenient to move

● **Condenser with filter**, easy to clean and maintain


● Rear of cabinet with **two sliding doors** for user operation

● **Automatic evaporation** for defrosting water, energy saving and environmental protection

● **Heat dissipation:** rear air intake and rear air discharge

Rough-In Data

Specifications subject to change without notice.

Model	Doors	Shelves	Cabinet Dimensions (inches) (mm)			CAP. CU.FT. LITER	Power KW	Voltage	Amps	NEMA Config.
			L	D	H					
NDC-36-SG	2	2	35.4 900	29.1 740	53.5 1360	14.7	0.65	115/60/1	7.6	5-15P 



DOE NRCAN