

**Model:**  
**NOM-40-S**

# Open Chiller



## NOM-40-S

### ● Cabinet Construction

Exterior- black brushed stainless steel, high-end and elegant; Interior-mirror s/steel 304, for food sanitation; Foamed with polyurethane, high-density insulation of inner cabinet

● Two sides are **tempered transparent glass** for high visibility

● **Refrigeration system:** two compressors, ventilation and strong cooling; environment-friendly **R290** refrigerant; temperature setting is 34°F to 41°F (2°C to 5°C). It is recommended to be used indoors where ambient temperature and relative humidity do not exceed 75° F(24°C) and 55%.

● **Digital temperature controller** with two probes assuring defrost control

● **Anti-corrosion coated evaporator**

● **Shelf:** stainless steel solid shelf, strong bearing, the height and angle are adjustable.

● **Highlight LED light** under each shelf, 6500k, energy-saving

● **Heavy duty caster**, convenient to move

● **Condenser with filter**, easy to clean and maintain


● With pulling type **night curtain**

● **Absorbent paper type of automatic evaporation** for defrosting water, energy saving and environmental protection

● **Heat dissipation:** front air intake and rear air discharge

### Rough-In Data

Specifications subject to change without notice.

Model	Doors	Shelves	Cabinet Dimensions (inches)			CAP. CU.FT. LITER	Power KW	Voltage	Amps	NEMA Config.
			L	D	H					
NOM-40-S	0	4	39.4 1000	27.6 700	78.7 2000	18	1.4	115/60/1	14	5-20P 



# NOM-40-S Plan View

